## **HAMMERHEAD SWING ARM CLICKER PRESS**

## **BODY TYPE A - DATA SHEET**

sales@americanclickerpress.com | www.americanclickerpress.com | (801) 613-7997 ext: sales

Dual Safety Operation Handles

Machined Aluminum Plate

Custom Hydraulic Ram

Polypropelene Cutting Board

Motor Start Switch

## **DESIGN, USE, AND FEATURES:**

- Two-button operational controls
- Compression counter

**Maximum Cutting Force** 

- Head swivels easily to reduce operator fatigue
- Spring-loaded head (head will not lower after powered down)
- Ships with Free Polypropylene cutting board
- Time-based cutting depth
- Single chamber design for easy access to oil and other components

15 Tons

• Energy Efficient

<b>y</b>	11 11111	11 11111
Model #:	HH-SA-10-A	HH-SA-15-A
Head Dimensions:	13.75" W x 17.5" D	15.75"W x 18.5" D
Table Dimensions:	31.5" W x 15.75" D	35.25" W x 16.25"
Max Die Dimensions:	13.75" x 15.75"	16.25" x 15.75"
Stroke Adjustment:	1.5" - 4.75"	1.5" - 5"
Daylight:	4.75"	5"
Motor Power:	1 HP [0.75KW]	1.5 HP [1KW]
Electrical Power Supply:	220V, 3PH, 60HZ	220V, 3PH, 60HZ
	480V, 3PH, 60HZ	480V, 3PH, 60HZ
Gross Crated Weight:	1600 LBS	1800 LBS
Shipping Dimensions:	40"W x 40"D x 65"H	40"W x 40"D x 65"H
Cutting Pad:	1" Thick Polypropylene	1" Thick Polypropylene
AW 46 Hydraulic Oil:	~ 9 Gallons*	~ 9 Gallons*

10 Tons

<sup>\*</sup>The final amount of oil should rest approximately 1" above the oil filter