

# HAMMERHEAD SWING ARM CLICKER PRESS

## BODY TYPE B - DATA SHEET

sales@americanclickerpress.com | www.americanclickerpress.com | (801) 613-7997 ext: sales



### DESIGN, USE, AND FEATURES:

- Two-button operational controls- must be pressed within .25 seconds of each other.
- Head swivels easily to reduce operator fatigue
- Hydraulic-controlled height adjustment (head will lower slowly after press is powered down)
- Ships with Free Polypropylene cutting board
- Time and pressure-based cutting modes
- Two chamber design for proper ventilation and easy access to motor and electronics
- Energy Efficient

Maximum Cutting Force	20 Tons	25 Tons	30 Tons
-----------------------	---------	---------	---------

Model #:	HH-SA-20-B	HH-SA-25-B	HH-SA-30-B
Head Dimensions:	14.5" W x 19" D	19.5" W x 22" D	24" W x 24" D
Table Dimensions:	35.5" W x 17" D	39.5" W x 19.5"	39.5" W x 19.5" D
Max Die Dimensions:	14.5" x 17"	19.5" x 19.5"	24" x 19.5"
Stroke Adjustment:	1.5" - 5"	1.5" - 5"	1.5" - 5"
Daylight:	5"	5"	5"
Motor Power:	1.5 HP [1.1KW]	2 HP [1.5KW]	2 HP [1.5KW]
Electrical Power Supply:	220V, 3PH, 60HZ 480V, 3PH, 60HZ	220V, 3PH, 60HZ 480V, 3PH, 60HZ	220V, 3PH, 60HZ 480V, 3PH, 60HZ
Gross Crated Weight:	2000 LBS	2600 LBS	3000 LBS
Shipping Dimensions:	48"W x 48"D x 65"H	48"W x 48"D x 65"H	48"W x 48"D x 65"H
Cutting Pad:	1" Thick Polypropylene	1" Thick Polypropylene	1" Thick Polypropylene
AW 46 Hydraulic Oil:	~ 7 Gallons*	~ 10 Gallons*	~ 10 Gallons*

\*The final amount of oil should rest approximately 1" above the oil filter